

## 6: Specifications

---

- Type:  
Push-pull Electrostatic Oval Shaped Units. Open Back Enclosure
- Frequency Response:  
7~41,000Hz
- Electrostatic Capacity:  
120pF(Lambda-Nova BASIC,  
Lambda-Nova CLASSIC),  
110pF (Lambda-Nova Signature)  
including cable provided respectively
- Impedance:  
133k $\Omega$  (Lambda-Nova BASIC,  
Lambda-Nova CLASSIC),  
145k $\Omega$  (Lambda-Nova Signature) at  
10kHz including cable provided respectively
- Sensitivity:  
100dB/100V r.m.s. Input/1kHz
- Maximum Output Sound Level:  
118dB/400Hz
- Standard Bias Voltage:  
580V/DC
- Left/Right Indication:  
L & R indicators are provided on the  
HEAD SPRING (ARC) and the left  
channel cable is marked with a solid line  
while the right channel cable is marked  
with a dotted line.
- Ear Pads:  
High quality synthetic leather
- Cable:  
6-core parallel low capacitance wire/2.5m  
(98-inch), (Special low capacitance  
Cable; Lambda-Nova Signature)
- Cable Conductor:  
OFC; Lambda-Nova BASIC, PC-OCC  
(Pure Crystal Ohno Continuous Casting);  
Lambda-Nova CLASSIC & Lambda-Nova  
Signature
- Weight:  
440g (472g; Lambda-Nova Signature),  
295g for body only (without cable)

\* Specifications and appearance due to Improvements are subject to change without notice.

## 6: 規格

---

- 形式: プッシュプル・エレクトロスタティック (静電型) 長円形発音体、後方解放型エンクロージャー (ケース)
  - 再生周波数帯域:  
7~41,000Hz
  - 静電容量:  
120pF; Lambda-Nova BASIC, Lambda-Nova CLASSIC ( 附属コードを含む )、  
110pF; Lambda-Nova Signature  
( 附属コードを含む )
  - インピーダンス:  
133k $\Omega$  (Lambda-Nova BASIC、  
Lambda-Nova CLASSIC、  
145k $\Omega$  (Lambda-Nova Signature) 10kHz に  
て附属ケーブルを含む )
  - 音圧感度:  
100dB/100V r.m.s. 入力/1kHz
  - 最大音圧レベル:  
118dB/400Hz
  - 成極電圧:  
580V/DC ( 標準 )
  - 左右チャンネル表示:  
ヘッドスプリングに L/R の表示 および  
コードに実線 (左)、点線 (右) の表示
  - イヤーパッド:  
高級人工皮革 (CLASSIC および Signature  
は高透湿性素材)
  - コード:  
6 芯平行低容量ケーブル/全長 2.5m、  
特製幅広低容量ケーブル: Lambda-  
Nova Signature
  - コード導体:  
OFC; Lambda-Nova BASIC、  
PC-OCC; Lambda-Nova CLASSIC、  
Lambda-Nova Signature
  - 重量:  
440g (472g; Lambda-Nova Signature)、  
本体のみ: 295g
- \* 規格および外観は改良のため予告無く変更することがあります。