

- RECOMMENDED ENVIRONMENT : 0°C ~40°C (32°F~104°F)
20%~70% RELATIVE HUMIDITY (NO ICING CONDITION)
- LEFT/RIGHT INDICATION : INNER SIDE of the EAR-PIECE + 3-DOTS for LEFT, RED BAND on the CABLE for RIGHT
- RUBBER EAR FITTING ADAPTOR : MADE of SILICON RUBBER/3-SIZES (LARGE/MEDIUM/SMALL)
- CORD : 6-CORE PARALLEL/1.5m(4 feet 11 inches)/OFC
- WEIGHT & SIZE : 28g with CORD, 12g without CORD, 28mm DIAMETER (0.9 ounce with CORD, 0.39 ounce without CORD, 1.1 inch DIAMETER)

*** S-001 * (Driver Unit)**

- TYPE: DRIVER UNIT for ELECTROSTATIC EARSPEAKERS
 - FREQUENCY RESPONSE : 5~20kHz/+0, -3dB (10V r.m.s. output driving 1:S-001)
 - GAIN : 54dB (500 times by VOLTAGE)
 - HARMONIC DISTORTION : 0.1% (1kHz/100V r.m.s. output driving 1:S-001)
 - INPUT IMPEDANCE : 10kΩ
 - STANDARD INPUT LEVEL : 100mV (0.1V) for 50V output
 - MAXIMUM OUTPUT LEVEL: 240V r.m.s. /1kHz
 - POWER CONSUMPTION : 1.3W/4.5V (AC/DC ADAPTOR OPERATION), 0.8W/3V (BATTERY OPERATION)
 - MINIMUM VOLTAGE for OPERATION : 2.05V (INDICATED by RED LED instead of GREEN)
 - RECOMMENDED ENVIRONMENT : 0~40°C (32°F~104°F) 20%~70% RELATIVE HUMIDITY (NO ICING CONDITION)
 - SIZE : 60mm(W) × 24mm(H) × 120mm(D)
(2.3 inch (W) × 0.94 inch (H) × 4.7 inch(D))
 - WEIGHT : 102g without BATTERIES, 140g with 2 DRY CELL BATTERIES (3.28 ounce without BATTERIES, 4.5 ounce with 2 DRY CELL BATTERIES)
 - BATTERY SIZE: AA (RECHARGEABLE or NON-RECHARGEABLE × 2-pcs)
- * Specifications & appearance are subject to change without prior notice

外観、規格などは予告なく変更することがございます。あらかじめご了承ください。

STAX[®]

スタックス工業株式会社 / STAX INDUSTRIES. LTD., TOKYO JAPAN
〒354 埼玉県入間郡三芳町上富 430 TEL:0492-58-3988, FAX:0492-58-2659
430 Kamitomi, Miyoshi-cho, Iruma-gun, Saitama Prefecture, Japan 〒354

Printed in Japan 95-11-1K MN ©STAX